



STORZ HYDRANT CONVERTER

SPECIFICATIONS SHEET



PART #: ZSZMC5045-2

5" STORZ METAL FACE X 4 1/2" NH
Female, (2) Set Screws and Standard
Storz Cap

STORZ X NH THREAD HYDRANT CONVERTER WITH LOCKING SET SCREWS

Aluminum Alloy 6061-T6 extruded forging only.
(2) stainless steel set screws for mounting. Set screws shall be mounted 180 degrees apart. The converter shall have a hard anodized aluminum metal face seal and hard anodized aluminum Storz ramp and lugs. The NH thread female adapter shall contain a flat rubber gasket which seals against the male hydrant nozzle. No castings acceptable

STORZ CAP AND CABLE

Both the center cap and the outer assembly containing the Storz ramps and lugs shall be Aluminum alloy 6061-T6 forged extrusion only. No castings acceptable.
The high torque, anti theft cap shall require a Storz wrench for removal. A .125" stainless steel coated cable must be supplied with the cap. Once installed, the Storz Hydrant Converter with cap extends less than 3" from the hydrant nozzle.

FINISH: All aluminum parts Hardcoat Anodized to Mil-A-8625-F, Type 3—dark grey



75 Highland Drive • Putnam, CT 06260
TEL: 800-420-4673 • FAX: 800-772-0255
www.kocher.com