



STORZ HYDRANT CONVERTER WITH HYDRANT NUT CAP *SPECIFICATIONS SHEET*



PART #: SZMC5045-3-Y

5" STORZ METAL FACE X 4 1/2" NH Female, (3) Set Screws, Hi-Visibility reflective tape, with low profile Hydrant Nut Storz Cap

STORZ X NH THREAD HYDRANT CONVERTER WITH LOCKING SET SCREWS

Aluminum Alloy 6061-T6 extruded forging only.
(3) stainless steel set screws for mounting. The Storz adapter shall have a powder coated aluminum metal face seal and powder coated aluminum Storz ramp and lugs. No castings acceptable. The NH thread female adapter shall contain a flat rubber gasket which seals against the male hydrant nozzle. Head must have relief machine cut around the outside to allow for recessed insertion of reflective tape. The relief shall measure 1/2" in width. Tape shall be yellow "3M" brand.

STORZ HYDRANT NUT CAP AND CABLE

The center assembly and the outer assembly containing the Storz ramps and lugs shall be Aluminum alloy 6061-T6 forged extrusion only. No castings acceptable. The outer assembly of the cap shall be smooth without lugs or ribs. The center assembly shall have a high torque hydrant nut head which can be removed with a standard hydrant wrench. A .125" stainless steel coated cable must be supplied with the cap.

FINISH: All metal parts shall be finished with corrosion resistant powder coating.



75 Highland Drive • Putnam, CT 06260
TEL: 800-420-4673 • FAX: 800-772-0255
www.kocher.com